

WALL PAPER Technical Spec

Item	Value or Conclusions	
MATERIAL	Composition	Paper coated with PVC
	Total Thickness	300micron (0.3mm)
	Weight	250g/m2
Storage Period	1year (Storage temperature of 22°C, relative humidity of 0 ~ 50%)	
APPLICATION	Eco-Solvent, Solvent ,Latex	
Width	0.53m/1.06m	
Length	50m	
Remark	There's 2% color difference between each of batches.	

Introduction of wallpaper character

1. The wallpaper was used for interior decoration. The product was strictly produced according to wallpaper industry's standard. We launched the wallpaper into the market after get the standard's approval. (Wallpaper Industry standard: GB18585-2001 , QB/T3805-1999,GB/T240-93.etc.)
2. The usage of the material should be made as long as the material has stayed at the printing place for at least 48 hours so that it has recaptured the requested balance with the environment (dimensions' stability, tension control, etc).
3. Because you are using the wallpaper for other purpose, pls do not test it by other industry's standard. And please accept its original character and using effects.

Worldwide Offices

United Kingdom Cgate UK Ltd., 788-790 Finchley Road, London, NW11 7TJ, ENGLAND
USA 2915 Pass a Grille Way, St. Pete Beach, FL 33706, Cellphone: +1 (617) 429 6056, Tel: +1 (727) 367 9793, Fax: +1 (501) 642 8828
China 7F B1, Junyao International Plaza, No.789 Zhaojiabang Road, Shanghai, P.R.C. Tel: 86-21-64229726/7/8, Fax: 86-21-6422972